

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
14 February 2002 (14.02.2002)

PCT

(10) International Publication Number  
**WO 02/12414 A1**

(51) International Patent Classification<sup>7</sup>: C09K 7/00, 7/02

(21) International Application Number: PCT/NL01/00586

(22) International Filing Date: 31 July 2001 (31.07.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
00202756.3 3 August 2000 (03.08.2000) EP

(71) Applicant (for all designated States except US): HANSE-  
LAND B.V. [NL/NL]; Zemikepark 8, NL-9747 AN  
Groningen (NL).

(72) Inventor; and

(75) Inventor/Applicant (for US only): STÖVER, Bernhard,  
Emile [NL/NL]; Frieselaan 4, NL-9765 CZ Paterswolde  
(NL).

(74) Agent: PRINS, A., W.; Verenigde, Nieuwe Parklaan 97,  
NL-2587 BN The Hague (NL).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK,  
SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA,  
ZW.

(84) Designated States (regional): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian  
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European  
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,  
IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF,  
CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD,  
TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: DRILLING FLUID COMPRISING A HIGH-AMYLOSE STARCH

(57) Abstract: The invention relates to drilling fluids used in methods for drilling wells into subterranean formations containing oil, gas or other minerals for the purpose of extraction and production of said minerals and the use of starch in such fluids. The invention provides a method for drilling such a well using a drilling fluid comprising a high-amylose starch or starch-blend.

WO 02/12414 A1

## Drilling fluid comprising a high-amylose starch

The invention relates to drilling fluids used in methods for drilling wells into subterranean formations containing oil, gas or other minerals for the purpose of extraction and production of said minerals and the use of starch in such fluids.

Drilling fluids used in methods for drilling production wells are often composed of water to which a wide array of additives, and different combinations thereof, are added to give a drilling fluid the characteristics required for the specific purposes for and circumstances under which it is used. Drilling fluids are for example used to clean and cool the drill bit and to flush to the surface the rock cuttings, stones, gravel, clay or sand that are torn loose by the drill bit. Another purpose is use for minimising formation damage by lining or plastering the walls of the wellbore to prevent caving in and to prevent invasion of solids and liquid into permeable formations, by bridging and sealing with drilling fluid components.

Specific components or additives of drilling fluids are for example properly graded or sized clay (i.e. bentonite or attapulgite clay), salts, silicates, brine, NaCl, CaBr<sub>2</sub>, ZnBr<sub>2</sub>, NaOH, or others that influence for example solids content, saturation, specific gravity, viscosity and plastering capacities of the fluid. Clay is especially useful since it plasters well and provides a drilling fluid with the necessary viscosity (carrying capacity) to suspend solids and thus carry ground material from out of a wellbore. With the increase in offshore drilling operations, the use of sea water in drilling fluids has increased greatly. This poses extra problems because of its high salinity and the presence of bivalent ions. Other additives, often applied at a lesser concentration than those mentioned above, are specifically added to improve plastering capacities and rheological properties of the fluid. Furthermore, salinity causes the filtration rate of clay suspensions to be high, necessitating the addition of fluid-loss reducing chemicals to keep fluid losses at bay. Examples of such additives are starches obtained from corn or

potatoes, and other polysaccharide polymers such as cellulose, as for example discussed in WO99/64356.

High-amylose starches are generally thought to not mix well with oils in preparing emulsions, as for example shown in US 5,882,713 and US 5,676,994. Corn or potato starches, both of the common variety containing both amylose and amylopectine, and of the waxy variety, containing virtually only amylopectine molecules (e.g. 0-5% amylose), and generally chemically cross-linked, are widely used in drilling fluids, for example in EP 0 852 235 a high-amylopectine (>80%) drilling fluid is used as water binding compound to reduce or counter fluid loss and to increase viscosity in general.

However, it is well known that organic polymers such as cellulose or starch tend to degrade when held at elevated temperatures for extended periods of time. These drilling-fluid additives are in general only effective up to temperatures of 100°C. The trend towards drilling deeper and thus hotter wells has led to the introduction of synthetic fluid-loss reducers (such as vinylamide, vinylsulphonate or vinylsulphonic acid) which are claimed to be more effective at high temperatures such as at 120-150°C. However, these synthetic fluid-loss reducing agents are in general much more expensive than the earlier mentioned starches. Furthermore, there is a distinct need to drill even deeper wells, and, consequently, a distinct need for fluid-loss reducers with even higher resistance towards high temperatures.

Also, the presence of chemical cross-linkers, such as epichlorohydrine, in chemically modified or cross-linked starches, is often seen as undesirable from the perspective of environmental requirements, and the present synthetic fluid-loss reducers are often also been considered to have disadvantages from the environmental perspective.

The invention provides a method for drilling a well into subterranean formations containing oil, gas or other minerals using a drilling fluid comprising a high-amylose starch or starch-blend. In general starches

contain two types of glucose polymers. Amylose is a predominantly linear chain molecule and amylopectin is a branched polymer of glucose. Drilling fluids that are commonly used comprise corn or potato starch having normal, i.e. approximately 24-27% or 20-22% respectively, amylose content, or the waxy versions thereof that in general contain below 5% amylose. For the purpose of the invention, any starch comprising more amylose than 27-28% is defined as high-amylose starch.

In a preferred embodiment, the invention provides a method wherein said starch or blend comprises at least 30% amylose, preferably at about 32-37% amylose when legume starches are used or at least 35% starch when mixtures with high-amylose corn starch are prepared, thus substantially higher than current starches used in drilling fluids. Such starches can be obtained by blending normal-amylose content starches with amylose derived from for example distinct corn varieties or other plants that contain more amylose than in general is found. A distinct corn variety is known that contains about 70% amylose in its starch, and by blending such a starch with commonly known starches, starch blends with amylose percentages higher than 35% are within easy reach. Also, various legume varieties, such as peas, beans or lentils are known that have amylose contents exceeding 30%, and starches derived from legumes thus easily can be used within a method as provided by the invention. Legume starches used according to the invention display especially useful high tolerance against the high temperature conditions found when drilling deeper wells. Other starches with high-amylose content, such as ginger starch, galangal root starch or chufa nut starch, are known in the art as well and can be used according to the invention. Of course, it is not preferred to make blends with the waxy type starches comprising no or only little amylose, although for some uses blending in some waxy starch need not be excluded, considering rheological properties of some of those amylopectine starches.

In a further preferred embodiment, the invention provides a method wherein said starch or starch blend is physically modified. Such physical modification can for example comprise extrusion. Surprisingly it was found that by using a method or drilling fluid as provided by the invention, substantially higher resistance against elevated temperatures (shown for example by only slight or minimal reductions of viscosity and/or fluid loss detectable after treatment at elevated temperatures) is achieved, even without having to chemically cross-link or in any other way chemically modify or stabilise the starch. Therewith, the invention provides a drilling fluid having resistance against elevated temperatures such as 110, 130, 150 or even 170 °C, values hitherto unknown for starches nor having been chemically cross-linked and/or stabilised. Chemical modification may still be advantageous when producing starches or blends for drilling fluids according to the invention having even higher or further resistance against elevated temperatures or other required characteristics obtainable via chemical modification, but initially, the invention provides the insight that chemically cross-linking or stabilising is not *ab initio* required to provide the desired higher resistance against elevated temperatures for starches in drilling fluid.

Preferably, the invention provides a method or drilling fluid comprising use of a high-amylose starch that has been physically modified by extrusion in for example a single or double screw extruder. Extrusion cookers or extruders in general are composed of several components: A live bin which provides a buffer stock of raw material at the extruder inlet; a variable speed feeding screw which meters raw material into the extruder barrel at a predetermined rate; an optional preconditioning cylinder which injects steam and/or water into the powdered ingredients and allows the mixture to at least partially equilibrate; and the extruder barrel. The extruder barrel consists of the chamber walls, which enclose the screw(s) and the material as it is being processed, jacketed heads, and rotating

screw(s). The extruder heads in general have jackets containing circulating steam, water or other heat transfer mediums, which permit adjustment of the temperature along the barrel. The diameter of the extruder cavity may be uniform throughout its length, or it may be tapered (decreasing in diameter) from front to back; some of the sections may be tapered while others are not. In general the barrel is capped with a die plate containing one or several orifices through which the extrudate is forced. Extrusion variables known in the art are within the method of feeding and pre-conditioning of the starch; within the method and point of moisture application, within control of temperature and moisture content of starch entering the extruder; within control of temperatures within each extruder section; within control of the point within the extruder where maximum dough viscosity is attained; within control of extrusion speeds; within control of time and temperature relationships within each section of the extruder; within control of the time within which product temperatures are elevated to maximum extrusion temperatures; within control of final extrusion temperatures; within selection of the shaping and sizing devices; within selection of the type, dwell time, drying temperature and velocities within the dryer and the cooler and the final product moisture.

Such extrusion can occur under wet or semi-wet conditions but dry or semi-dry extrusion is preferred, if only because less volume needs to be treated. To further generate temperature resistance, said starch or starch blend can of course comprise a chemically cross-linked starch, either a blended in fraction or the total fraction can optionally be cross-linked and/or stabilised by one of the various method known in the art.

Furthermore, the invention provides drilling fluid (herein also referred to as mud composition) for use in a method according to the invention comprising a high-amylose starch as defined herein. Also, the invention provides a starch or starch blend for use in a drilling fluid according to the invention, preferably a high-amylose starch that has been

physically modified by for example extrusion in a single or double screw extruder. Such as starch is preferably at least partly derived from a high-amylose corn starch or from a legume. The invention is further explained in the detailed description herein.



Examples of mud compositions or drilling fluids according to the invention.

5	<u>Mud composition I</u>		Fresh water		
			NaCl	40 kg/m <sup>3</sup>	14ppb
			Sodium Bicarbonate	2.9 kg/m <sup>3</sup>	1ppb
			Bentonite	100 kg/m <sup>3</sup>	29ppb
			Product	9 kg/m <sup>3</sup>	3ppb
10	Results		<u>Apparent Viscosity</u>	<u>pH</u>	<u>API Fluidloss, ml</u>
	25 Celsius		10.0	8.3	6.0
	16 hrs, 140 Celsius		7.0	8.2	6.0
15	<u>Mud composition II</u>		Sea water		
			Sodium Bicarbonate	2.9 kg/m <sup>3</sup>	1ppb
			Attapulgate	40 kg/m <sup>3</sup>	14ppb
			Product	15 kg/m <sup>3</sup>	5ppb
20	Results		<u>Apparent Viscosity</u>	<u>pH</u>	<u>API Fluidloss, ml</u>
	25 Celsius		26	8.2	8.2
	16 hrs, 140 Celsius		10	8.1	8.4
25	<u>Mud composition III</u>		Fresh water		
			NaCl(Saturated)	400 kg/m <sup>3</sup>	140ppb
			Sodium Bicarbonate	2.9 kg/m <sup>3</sup>	1ppb
			Bentonite	50 kg/m <sup>3</sup>	17.5ppb
			Product	15 kg/m <sup>3</sup>	5ppb
30	Results		<u>Apparent Viscosity</u>	<u>pH</u>	<u>API Fluidloss, ml</u>
	25 Celsius		9.0	8.1	2.0
	16 hrs, 140 Celsius		7.5	7.8	3.5
35					
40					
45					

<u>Mud composition IV</u>		
	Fresh water	
	NaCl	40 kg/m <sup>3</sup>
5	Sodium Bicarbonate	2.9 kg/m <sup>3</sup>
	Bentonite (OCMA Clay)	100 kg/m <sup>3</sup>
	<i>Product</i>	9 kg/m <sup>3</sup>
10	Results	
	<u>Apparent Viscosity</u>	<u>API Fluidloss, ml</u>
	25 Celsius	10.0
	16 hrs, 160 Celsius	6.0
15	Note: <i>Product</i> herein comprises a high-amylose legume starch comprising at about 32% amylose. API fluidfloss was determined according to the guidelines of the American Petroleum Institute. Control compositions comprising normal starch containing about 35% amylose instead of <i>Product</i> maintained integrity at treatments up to about 110 °C, but disintegrated	
20	after 16 hrs, 160 Celsius, whereby fluid losses of more than 40 ml were observed.	

Temperature Tolerance Extruded Legume Starch

## Test results

5

Composition; 4% NaCl, 100 gr OCMA clay Starch at 10 gr/l	Temp °C	FANN reading rpm 1.0 spring										API	
		600	300	200	100	60	30	6	3	Pv cp	Yp lbs/100 ft <sup>2</sup>	Fluidloss Ph ml	
Yellow Pea Starch (Canada)	150 8.1	12	10	8	5	-	-	1.5	1	2	8	7.5	
Faba Bean Starch (Canada)	150 1.5	13 1	10 3	8 7	5 9.0	-	8.2						
Great White Bean Starch (Canada)	150 8.2	14	10	7	5	-	-	2	1.5	4.0	6.0	9.0	
Urad pea starch (India)	150 8.1	35	21	14	9	-	-	3	2.5	13.5	8.0	8.0	

Claims

1. A method for drilling a well into subterranean formations containing oil, gas or other minerals using a drilling fluid comprising a high-amylose starch or starch-blend.  
5
2. A method according to claim 1 wherein said starch or blend comprises at least 30% amylose.
3. A method according to claim 1 or 2 wherein said starch or blend is at least partly derived from corn.
- 10 4. A method according to claim 1, 2 or 3 wherein said starch or blend is at least partly derived from a legume.
5. A method according to anyone of claims 1 to 4 wherein said starch or blend is physically modified.
6. A method according to any of claims 1 to 5 wherein said starch or starch  
15 blend comprises a crosslinked starch.
7. A method according to any of claims 1 to 6 wherein said starch is stabilised.
8. A drilling fluid comprising a high amylose starch.
9. A drilling fluid according to claim 8 comprising a starch or starchblend  
20 comprising at least 30% amylose.
10. A drilling fluid according to claim 8 or 9 comprising corn or legume starch.
11. Use of a high-amylose starch or starch-blend for the preparation of a drilling fluid.
- 25 12. Use of a high-amylose starch or starch-blend in a method for drilling a well into subterranean formations.
13. Use according to claim 11 or 12 wherein said starch or blend comprises corn or legume starch.

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 C09K7/00 C09K7/02

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 C09K E21B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 852 235 A (CHEMSTAR PRODUCTS COMPANY) 8 July 1998 (1998-07-08) page 3, line 13 - line 23; claims 10-14	1,3,5-8, 10-13
X	US 5 882 713 A (ESKINS KENNETH ET AL) 16 March 1999 (1999-03-16) column 14, line 11 - line 14; claim 26; example 16	1-3,5-13
X	US 5 676 994 A (ESKINS KENNETH ET AL) 14 October 1997 (1997-10-14) column 12, line 15 - line 18; example 16	1-3,5-13
X	WO 99 64356 A (POTTER LEON J ; HENSLEY GARY L (US)) 16 December 1999 (1999-12-16) page 13 -page 19; tables 1-4	1-3,5-13
	-/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

## \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*G\* document member of the same patent family

Date of the actual completion of the international search

8 November 2001

Date of mailing of the international search report

15/11/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5618 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax (+31-70) 340-3016

Authorized officer

olde Scheper, B

## INTERNATIONAL SEARCH REPORT

International Application No.  
PCT/NL 01/00586

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages.	Relevant to claim No.
A	R.L.WHISTLER (ED.): "Industrial Gums" 1973 , ACADEMIC PRESS , NEW YORK XP002161137 page 545 -page 557	1-13

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No.

PCT/NL 01/00586

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0852235	A	08-07-1998	US 5851959 A	22-12-1998
			EP 0852235 A2	08-07-1998
US 5882713	A	16-03-1999	US 5676994 A	14-10-1997
			AU 698729 B2	05-11-1998
			AU 2425995 A	16-11-1995
			BR 9507574 A	09-09-1997
			CA 2188596 A1	02-11-1995
			EP 0758198 A1	19-02-1997
			JP 11514202 T	07-12-1999
			NZ 285224 A	26-06-1998
			WO 9528849 A1	02-11-1995
US 5676994	A	14-10-1997	US 5882713 A	16-03-1999
			AU 698729 B2	05-11-1998
			AU 2425995 A	16-11-1995
			BR 9507574 A	09-09-1997
			CA 2188596 A1	02-11-1995
			EP 0758198 A1	19-02-1997
			JP 11514202 T	07-12-1999
			NZ 285224 A	26-06-1998
			WO 9528849 A1	02-11-1995
WO 9964356	A	16-12-1999	US 5997652 A	07-12-1999
			US 6177014 B1	23-01-2001
			US 6155964 A	05-12-2000
			AU 4682799 A	30-12-1999
			WO 9964356 A1	16-12-1999